



German
Design Award
SPECIAL
MENTION 2014

PIA'13 PRODUCT INNOVATION
AWARD WINNER

DESIGN PLUS

KWC-No.	Finish
10.201.102.127FL	decor steel
A 215, flexible connection hoses	

Kitchen

Lever mixer

- Lever installation only possible on the right side
 - Child safety: cold water flow in lever position towards the front
- gap between wall and centre of mounting hole min. 42 mm
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Covered pull-out spray
 - ergonomic spout alignment, shape and handling
 - SprayClean - easy to clean and actively prevents limescale buildup
 - Neoperl® Cascade®
 - PowerClean - needle spray mode, with automatic diverter reset
 - up to 500 mm pull-out length
 - hose surface to fit faucet surface
- SwivelStop - hose guide, swivelling 270° , limitable to 120°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge S 25
 - with ceramic discs
 - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm

Flow rate normal spray 8 l/min (3 bar)
Flow rate needle spray 9 l/min (3 bar)
Acoustic group II

Subject to technical, range and model changes. Dimensions in mm.